

Door cores							
Thickness [mm]	Pressing Width [mm]				Weight		
					Type	kg/m <sup>2</sup>	kg/m <sup>3</sup>
9	2020				VL	5,0	560
9,3	2020				VL	5,2	560
10	1250	2020			VL	5,6	560
10	1250	2020			VV	6,3	630
10,6	1220	2020			VL	5,9	560
10,6	1220	2020			VV	6,7	630
11	1220	2020			VL	6,2	560
11	1220	2020			VV	6,9	630
12	1220	2020			VL	6,7	560
13	1220	2040			VL	7,3	560
13,5	2040				VL	7,6	560
16	2020				VL	8,3	520
16,5	2020				VL	8,6	520
19	1978				VL	9,9	520
23	1035				VL	11,3	490
32	1888	2090			VL	15,7	490
32	1888	2090			VT	13,4	420
32	1888	2090			VV	19,2	600
33	1265	1888	1958	2090	VL	16,2	490
33	1265	1888	1958	2090	VT	13,9	420
33	1265	1888	1958	2090	VV	19,8	600
34	2090				VL	16,7	490
34	2090				VT	14,3	420
34	2090				VV	20,4	600
38	1978	2050			VE	20,1	530
38	1978	2050			VE7	17,9	470
38	1978	2050			VL	18,6	490
38	1978	2050			VT	16,0	420
38	1978	2050			VV	23,6	620
42	1978				VL	20,6	490
42	1978				VT	17,6	420

Stile material							
Thickness [mm]	Pressing Width [mm]				Weight		
					Type	kg/m <sup>2</sup>	kg/m <sup>3</sup>
32	2090				HVA	20,8	650
32	2090				HVB	22,4	700
33	1958	2090			HVA	21,5	650
33	1958	2090			HVB	23,1	700
38	2050				VA	24,7	650